

Produkt: D5052

Hersteller: NITTO BELGIUM N.V.

Warengruppe: KLEBEBAND

Artikelgruppe: DOPPELSEITIG

Download: 17.04.2024

NITTO D5052

Dieses Datenblatt wurde Ihnen von der Firma tewipack Uhl GmbH zur Verfügung gestellt. Die Firma tewipack Uhl GmbH übernimmt keinerlei Verantwortung für die Aktualität und die Richtigkeit der enthaltenen Informationen. Die Eigenschaften der Produkte können sich aufgrund verschiedener Einflüsse wie beispielsweise Zusammensetzung und Zustand des Substrats, Unreinheiten in oder auf dem Substrat, Temperatur und Luftfeuchtigkeit bei der Lagerung und Umgebungsbedingungen während der Anwendung ändern. Bei Verwendung dieses Produkts in Kombination mit anderem Material ist der Kunde dafür verantwortlich, durch eigene Tests zu prüfen, ob das Produkt für die geplante Kombination geeignet ist und ob diese Kombination die erwarteten Ergebnisse liefert


Product: **D5052 - D5052H**

Product group: **Double Coated Tapes**

General description

Nitto double coated tape D5052 and D5052H consist of a non-woven carrier coated with a pressure sensitive modified acrylic adhesive, intended for use on different foams where high adhesion levels are required.

Construction



- Colourless modified acrylic adhesive
- Non-woven carrier
- Colourless modified acrylic adhesive
- Paper release liner

Characteristics

Nitto D5052(H) is intended for use as a foam lamination tape where a particular high adhesion level and temperature resistance is required.

The relative soft adhesive allows lamination on foams at room temperature.

Application

These products have been designed for lamination to a variety of PUR foams, impregnated foams and many other substrates such as textiles, fabrics, cork and felts.

Features

- high initial adhesion
- polyvalent on different foams
- different release liners
- RoHS compliant

Technical Properties

General physical properties

	Typical Value	Test Method
Adhesive type	Colourless modified acrylic adhesive	
Tape thickness*	0.145 mm	EN 1942
Release liner type	D5052: Siliconised white paper (120 g/m ²) D5052H: Siliconised havana paper (90 g/m ²)	
Carrier type	Non-woven	
Adhesion to BA steel	2000 cN/20mm	EN 1939
Release value	D5052: 40 cN/50mm D5052H: 35 cN/50mm	
Static shear	1.0 mm/2h	EN 1943
Transport and storage conditions	Temperature 15 to 30 °C Relative humidity 40 to 75% RH	

* Tape thickness = Total thickness without liner
Details from the test methods are described on the customer product specification.

Performance properties

Adhesion in cN/20mm					EN 1939
PMMA	PC	ABS	PET	PO-foam	PU-foam
1900	1900	1600	1400	1000	700
Weight Added Peel Off (WAPO)					2 h at 60°C, width 20mm, 100g
PP 220 mm/2h		ABS 220 mm/2h		BA 200 mm/2h	
Dynamic shear			600 N/cm ²		Tested after 15min., 300mm/min
Saft test			85 °C		+0,5°C/min., 15x15mm, 200g

Warranty

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 6 months thereafter, subject to the conditions set out herein.

Application guidelines

- For optimum results, an even rub down pressure must be applied to the taped area to create the best possible adhesion between tape and the substrates.
- To ensure optimal anchorage of tape to foam, attention should be paid to the lamination pressure, temperature and time.
- Remove the liner prior to usage.
- The tape should be applied to clean and dry surfaces.
- The best application conditions are obtained at a temperature between 15 °C and 40 °C.

If you require additional information on technical properties and application as well as product sampling or testing, please contact your local Nitto sales office.

General conditions of use and precautions:

The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage and the surrounding environment at and after application and time of exterior use.

When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

Packaging, transport and storage:

During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

Liability:

Except for its wilful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits.
The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product.

Product information:

This datasheet provides a general description of the product properties and application scope. Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

Please be advised that the information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

Edition: September 2013
Code: DS/07.10/E4 D5052 (H) ENG
This datasheet replaces all previous versions

Nitto Belgium NV has obtained following certificates:

- ISO 9001
 - ISO 14001
 - ISO/TS 16949
- Please check our website for applicable scope



For your local Nitto sales office, please visit our web site:
www.nitto.com

Copyright © 2016 NITTO BELGIUM NV. All rights reserved.