## Sicherheitsdatenblatt



Produkt: 639

Hersteller: PERMABOND ENGINEERING ADHESIVES

Warengruppe: KLEBSTOFF

Artikelgruppe: UV- AUSHÄRTENDER KLEBSTOFF

Download: 28.03.2024

PERMABOND UV639

Dieses Datenblatt wurde Ihnen von der Firma tewipack Uhl GmbH zur Verfügung gestellt. Die Firma tewipack Uhl GmbH übernimmt keinerlei Verantwortung für die Aktualität und die Richtigkeit der enthaltenen Informationen. Die Eigenschaften der Produkte können sich aufgrund verschiedener Einflüsse wie beispielsweise Zusammensetzung und Zustand des Substrats, Unreinheiten in oder auf dem Substrat, Temperatur und Luftfeuchtigkeit bei der Lagerung und Umgebungsbedingungen während der Anwendung ändern. Bei Verwendung dieses Produkts in Kombination mit anderem Material ist der Kunde dafür verantwortlich, durch eigene Tests zu prüfen, ob das Produkt für die geplante Kombination geeignet ist und ob diese Kombination die erwarteten Ergebnisse liefert



# SAFETY DATA SHEET Permabond UV639

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name Permabond UV639

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Permabond Engineering Adhesives Ltd.

Wessex Way Colden Common Winchester

Hampshire SO21 1WP United Kingdom

Tel: +44 (0)1962 711 661 Fax: +44 (0)1962 711 662 info.europe@permabond.com

#### 1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone CHEMTREC Ireland: +(353)-19014670

number CHEMTREC Australia: +(61)-290372994

CHEMTREC New Zealand: +(64)-98010034

## SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Corr. 1C - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 1B -

H360Df STOT SE 3 - H335

**Environmental hazards** Aquatic Chronic 2 - H411

#### 2.2. Label elements

## Hazard pictograms









Signal word

Danger

#### Permabond UV639

**Hazard statements** H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H360Df May damage the unborn child. Suspected of damaging fertility.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352a IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

Contains ISOBORNYL ACRYLATE, N,N-DIMETHYLACRYLAMIDE, TETRAHYDROFURFURYL

ACRYLATE, 2-HYDROXYETHYL METHACRYLATE

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with existing Community, National and

local regulations.

#### 2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

ISOBORNYL ACRYLATE 10-30%

CAS number: 5888-33-5 EC number: 227-561-6 REACH registration number: 01-

2119957862-25-XXXX

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Skin Sens. 1 - H317

STOT SE 3 - H335

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

## N,N-DIMETHYLACRYLAMIDE 10-30%

REACH registration exemption - < 1 tonne

Classification

Acute Tox. 3 - H301

Acute Tox. 3 - H311

Eye Dam. 1 - H318

#### Permabond UV639

#### TETRAHYDROFURFURYL ACRYLATE

10-30%

CAS number: 2399-48-6 EC number: 219-268-7 REACH registration number: 01-

2120738396-46-XXXX

Classification

Acute Tox. 4 - H302 Skin Corr. 1C - H314 Eye Dam. 1 - H318 Skin Sens. 1B - H317 Repr. 1B - H360Df Aquatic Chronic 2 - H411

#### 2-HYDROXYETHYL METHACRYLATE

10-30%

CAS number: 868-77-9 EC number: 212-782-2 REACH registration number: 01-

2119490169-29-XXXX

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

## DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE

1-5%

OXIDE

CAS number: 75980-60-8 EC number: 278-355-8 REACH registration number: 01-

2119972295-29-XXXX

Classification

Skin Sens. 1B - H317 Repr. 2 - H361f

Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

**Inhalation** Move the exposed person to fresh air. Get medical attention if any discomfort continues.

**Ingestion** Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water.

Give plenty of water to drink. Do not induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention promptly if symptoms occur after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Promptly wash eyes with plenty of

water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** Irritation of nose, throat and airway.

**Ingestion** Harmful if swallowed. May cause chemical burns in mouth and throat.

**Skin contact** Chemical burns. Mild dermatitis, allergic skin rash.

Eye contact May cause serious eye damage.

#### Permabond UV639

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations. Treat symptomatically.

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

products

Do not use water jet as an extinguisher, as this will spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Hazardous combustion

Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide,

and unknown hydrocarbons.

#### 5.3. Advice for firefighters

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for

disposal.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when

using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Protect against

direct sunlight. Never return unused material to storage receptacle.

#### 7.3. Specific end use(s)

Specific end use(s) Adhesive.

## SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

#### ISOBORNYL ACRYLATE (CAS: 5888-33-5)

**DNEL** Workers - Dermal; Long term systemic effects: 1.39 mg/kg/day

#### Permabond UV639

PNEC Fresh water; 0.001 mg/l

marine water; 0 mg/l

STP; 2 mg/l

Sediment (Freshwater); 0.145 mg/kg Sediment (Marinewater); 0.015 mg/kg

## N,N-DIMETHYLACRYLAMIDE (CAS: 2680-03-7)

**DNEL** Workers - Inhalation; Long term systemic effects: 0.207 mg/m³

Workers - Dermal; Long term systemic effects: 357 µg/kg/day

PNEC Fresh water; 0.12 mg/l

marine water; 0.012 mg/l

STP; 18 mg/l

Sediment (Freshwater); 0.509 mg/kg Sediment (Marinewater); 0.051 mg/kg

Soil; 0.031 mg/kg

## TETRAHYDROFURFURYL ACRYLATE (CAS: 2399-48-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 1.73 mg/m³

Workers - Dermal; Long term systemic effects: 4.9 mg/kg/day

PNEC Fresh water; 3.92 μg/l

marine water; 0.392 µg/l

STP; 2.637 mg/l

Sediment (Freshwater); 0.021 mg/kg, dw Sediment (Marinewater); 0.002 mg/kg, dw

Soil; 0.002 mg/kg, dw

Intermittent release; 39.2  $\mu g/l$ 

## 2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)

**DNEL** Workers, Industry - Inhalation; Long term systemic effects: 4.9 mg/m³

Workers, Industry - Dermal; Long term systemic effects: 1.3 mg/kg/day

PNEC Workers, Industry - Water; Long term 0.482 mg/l

Workers, Industry - Soil; Long term 0.476 mg/kg Workers, Industry - STP; Long term 10 mg/l Workers, Industry - Fresh water; 3.79 mg/kg

#### DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE (CAS: 75980-60-8)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.5 mg/m³

Workers - Dermal; Long term systemic effects: 1 mg/kg/day

PNEC Fresh water; 0.004 mg/l

marine water; 0 mg/l

Sediment (Freshwater); 0.29 mg/kg Sediment (Marinewater); 0.029 mg/kg

Soil; 0.056 mg/kg STP; >1000 mg/l

#### 8.2. Exposure controls

#### Permabond UV639

#### Protective equipment







Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

CONTROL OF SKIT CONTROL WILL THIS SUBSTR

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly

remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene

practices is required.

Respiratory protection Ensure adequate ventilation of the working area. Respiratory protection may be required if

excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Organic vapour filter. Type A. (EN14387)

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Clear.

Odour Acrylic

Odour threshold Not available.

**pH** Not relevant.

Melting point Not available.

Initial boiling point and range Not applicable.

Flash point >100°C

**Evaporation rate** Not available.

Upper/lower flammability or

explosive limits

Not available.

Vapour pressure Not available.

#### Permabond UV639

Vapour density Not available.

Relative density 1.0

Solubility(ies) Slightly soluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient Not available.

Auto-ignition temperature Not available.

Viscosity ≈1950 mPa s @ 25°C

Oxidising properties Not available.

9.2. Other information

Other information Not relevant.

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** The following materials may react with the product: Strong oxidising agents. Light.

10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

There are no known reactivity hazards associated with this product.

10.4. Conditions to avoid

Conditions to avoid Protect against direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong reducing agents. Strong oxidising agents.

#### 10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified

organic compounds.

#### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

Skin sensitisation

**Skin sensitisation** May cause sensitisation by skin contact.

Reproductive toxicity

Reproductive toxicity - fertility May damage fertility.

Reproductive toxicity -

May damage the unborn child.

development

Aspiration hazard

**Aspiration hazard** None under normal conditions.

#### Permabond UV639

**In high concentrations**, vapours may irritate throat and respiratory system and cause

coughing.

**Ingestion** Harmful if swallowed.

**Skin contact** This product is strongly irritating. Prolonged contact may cause burns.

**Eye contact** Causes serious eye damage.

Toxicological information on ingredients.

#### ISOBORNYL ACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀

5,000.0

mg/kg) Species

ecies Rat

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 3,000.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) No information available.

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye Not irritating.

damage/irritation

Skin sensitisation

**Skin sensitisation** Local Lymph Node Assay (LLNA) - : Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro** Genome mutation: Negative.

Carcinogenicity

**Carcinogenicity** No information available.

Reproductive toxicity

Reproductive toxicity -

Two-generation study - NOEC 0.092 mg/l, Inhalation, Rat P

fertility

Reproductive toxicity -

Developmental toxicity: - NOAEL: 500 mg/kg/day, Oral, Rat

development

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

## Permabond UV639

**Aspiration hazard** No information available.

N,N-DIMETHYLACRYLAMIDE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

216.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD50 519.0

mg/kg)

**Species** 

Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 vapours mg/l)

3.16

**Species** Rat

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Not irritating.

Serious eye damage/irritation

Serious eye

damage/irritation

Method: OECD 405, Rabbit Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation No data available.

Skin sensitisation

**Skin sensitisation** Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro**Gene mutation: Negative.

**Genotoxicity - in vivo** Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No data available.

Reproductive toxicity

Reproductive toxicity - Screening - NOAEL 30 mg/kg/day, Oral, Rat F1

fertility

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

TETRAHYDROFURFURYL ACRYLATE

## Permabond UV639

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

Species Rat

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) No information available.

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Corrosive.

928.0

Serious eye damage/irritation

Serious eye

Method: OECD 405, Rabbit Causes serious eye damage.

damage/irritation

Skin sensitisation

**Skin sensitisation** No information available.

Germ cell mutagenicity

**Genotoxicity - in vitro**Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity -

Screening - NOAEL >300 mg/kg/day, Oral, Rat P May damage fertility.

fertility

Reproductive toxicity -

development

May damage the unborn child.

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** No information available.

Aspiration hazard

**Aspiration hazard** No information available.

2-HYDROXYETHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅o

5,000.0

mg/kg)

**Species** Rat

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 5,000.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

#### Permabond UV639

Notes (inhalation LC<sub>50</sub>) No information available.

Skin corrosion/irritation

Animal data Erythema/eschar score: Very slight erythema - barely perceptible (1). Not irritating.

Serious eye damage/irritation

Serious eye Moderately irritating.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

**Skin sensitisation** Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro**Conclusive data but not sufficient for classification.

**Genotoxicity - in vivo** Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening - NOAEL >=1000 mg/kg/day, Oral, Rat F1

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: >=1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

**Aspiration hazard** Not applicable.

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

5,000.0

**Species** Rat

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.1

mg/kg)

**Species** 

)

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) No information available.

Rat

Skin corrosion/irritation

#### Permabond UV639

**Skin corrosion/irritation** Not irritating.

Serious eye damage/irritation

Serious eye

Not irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

Germ cell mutagenicity

**Genotoxicity - in vitro**Gene mutation: Negative.

Carcinogenicity

Carcinogenicity No data available.

Reproductive toxicity

Reproductive toxicity -

Possible risk of adverse reproductive effects.

fertility

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: 150 mg/kg, Oral, Rat

Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 50 mg/kg/day, Oral, Rat

Aspiration hazard

**Aspiration hazard** No data available.

#### SECTION 12: Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

12.1. Toxicity

**Toxicity** The mixture is classified based on the available hazard information for the ingredients as

defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the

substances listed under Section 3 is provided in the following.

#### Ecological information on ingredients.

#### ISOBORNYL ACRYLATE

Acute aquatic toxicity

**LE(C)**<sub>50</sub>  $0.1 < L(E)C50 \le 1$ 

M factor (Acute) 1

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 0.704 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 1.98 mg/l, Pseudokirchneriella subcapitata NOEC, 72 hours: 0.405 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

M factor (Chronic) 1

## Permabond UV639

Chronic toxicity - aquatic

NOEC, 21 days: 0.092 mg/l, Daphnia magna

invertebrates

#### N,N-DIMETHYLACRYLAMIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅o, 96 hours: > 120 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: > 120 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

NOEC, 72 hours: 50 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms

EC<sub>20</sub>, 3 hours: 430 mg/l, Activated sludge

## TETRAHYDROFURFURYL ACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 7.32 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 37.7 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: 3.92 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms

EC<sub>50</sub>, 3 hours: 263.7 mg/l, Activated sludge

#### 2-HYDROXYETHYL METHACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 100 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 380 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 836 mg/l, Selenastrum capricornutum NOEC, 72 hours: 400 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms

EC<sub>50</sub>, 16 hours: > 3000 mg/l, Pseudomonas fluorescens

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 24.1 mg/l, Daphnia magna

#### DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: 6.53 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 3.53 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: > 2.01 mg/l, Pseudokirchneriella subcapitata

#### Permabond UV639

Acute toxicity - microorganisms

EC<sub>50</sub>, 180 minutes: > 1000 mg/l, Activated sludge

#### 12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

#### ISOBORNYL ACRYLATE

**Biodegradation** Water - Degradation 57%: 28 days

N,N-DIMETHYLACRYLAMIDE

Stability (hydrolysis) pH7 - Half-life : > 1 year @ 50°C

Biodegradation Water - Degradation 0%: 28 days

2-HYDROXYETHYL METHACRYLATE

Biodegradation Water - Degradation 84%: 28 days

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

**Biodegradation** Water - Degradation < 20%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

## N,N-DIMETHYLACRYLAMIDE

Bioaccumulative potential No data available.

2-HYDROXYETHYL METHACRYLATE

Bioaccumulative potential BCF: 1.34 - 1.54,

## DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Bioaccumulative potential BCF: 23 - 55, Cyprinus carpio (Common carp)

12.4. Mobility in soil

**Mobility** No data available.

Ecological information on ingredients.

#### N,N-DIMETHYLACRYLAMIDE

**Mobility** No data available.

2-HYDROXYETHYL METHACRYLATE

Adsorption/desorption

coefficient

Water - Koc: 42.7 @ 20°C

#### Permabond UV639

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

#### N,N-DIMETHYLACRYLAMIDE

Other adverse effects No data available.

#### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local

regulations Empty containers may contain product residue; follow SDS and label warnings

even after they have been emptied.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances.

## SECTION 14: Transport information

#### 14.1. UN number

1760

#### 14.2. UN proper shipping name

CORROSIVE LIQUID, N.O.S. (contains Tetrahydrofurfuryl acrylate)

#### 14.3. Transport hazard class(es)

8

#### Transport labels



#### 14.4. Packing group

Ш

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



## 14.6. Special precautions for user

Not applicable.

**EmS** F-A, S-B

Tunnel restriction code (E)

#### Permabond UV639

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH)

**Guidance** Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Revision date 16/01/2020

Revision 1

Hazard statements in full H301 Toxic if swallowed.

H302 Harmful if swallowed. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H360Df May damage the unborn child. Suspected of damaging fertility.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.