

Produkt: 764

Hersteller: 3M DEUTSCHLAND GMBH

Warengruppe: KLEBEBAND

Artikelgruppe: EINSEITIG

Download: 18.04.2024

764 GENERAL PURPOSE VINYL TAPE

Dieses Datenblatt wurde Ihnen von der Firma tewipack Uhl GmbH zur Verfügung gestellt. Die Firma tewipack Uhl GmbH übernimmt keinerlei Verantwortung für die Aktualität und die Richtigkeit der enthaltenen Informationen. Die Eigenschaften der Produkte können sich aufgrund verschiedener Einflüsse wie beispielsweise Zusammensetzung und Zustand des Substrats, Unreinheiten in oder auf dem Substrat, Temperatur und Luftfeuchtigkeit bei der Lagerung und Umgebungsbedingungen während der Anwendung ändern. Bei Verwendung dieses Produkts in Kombination mit anderem Material ist der Kunde dafür verantwortlich, durch eigene Tests zu prüfen, ob das Produkt für die geplante Kombination geeignet ist und ob diese Kombination die erwarteten Ergebnisse liefert



764 General Purpose Vinyl Tape

Product Data Sheet

Updated : September 1999
Supersedes : New

Product Description A general purpose vinyl tape for use in non-critical applications such as colour coding, bundling and safety marking etc.

Physical Properties
Not for specification purposes

Adhesive Type	Rubber
Backing	Polyvinyl Chloride
Total Tape Thickness	5.0 mils (0.125mm) nominal
Tape Colour	Yellow, white, red, black, blue, transparent, green, orange, purple, grey, brown
Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity.

Performance Characteristics
Not for specification purposes

Adhesion to Stainless Steel ASTM D-3330	18 oz. / in. width 2.1 N/10mm	
Tensile Strength at Break ASTM D-3659	13 lbs. /in. 22.8 N/10mm	
Elongation at Break ASTM D-3659	180 %	

Date : September 1999
764 General Purpose Vinyl
Tape

General Information

- While vinyl tapes resist most common solvents, care should be taken to avoid ketones, chlorinated hydrocarbons and esters found in lacquers, thinners, degreasers, paint strippers, etc. which may cause the backing to swell or curl.
- Best results are attained when applied to clean, dry surfaces between 60°-85°F (15°-27°C)

Application Ideas

- General purpose holding and colour coding.
- Temporary marking of parts or machines.
- Protect parts, equipment or products from abrasion.

Features	Advantages	Benefits
Pigmented vinyl backing.	Readily conformable to many irregular surfaces.	Good for sealing.
	Abrasion resistant.	Helps provide surface protection.
Rubber adhesive.	Good instant adhesion.	Adheres well to many surfaces.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Tapes & Adhesives

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
3M House,
28 Great Jackson Street,
Manchester,
M15 4PA

Customer Service :
Tel 0161 236 8500
Fax 0161 237 1105

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

Customer Service :
Tel (01) 280 3555
Fax (01) 280 3509